

## AU-JET-L Series SELF-PRIMING PUMP

AU-JET-L series self-priming pumps are high efficient jetting pump with excellent suction even when there are air bubbles. The pump consists a single impeller, centrifugal pump and a nozzle with a jet pipe. The series pumps are particularly suitable for water supplying in domestic installations, small-scale agriculture watering and where self-priming operation is demanded.



### CONSTRUCTION:

#### PUMP Peripheral

Pump Body: Cast Iron  
Impeller: Brass / P.P.O. Plastics / Aluminum  
Mechanical Seal: Carbon / Ceramic / Stainless steel  
NOZZLE: P.P.O / Aluminum  
JET PIPE: P.P.O / Aluminum  
DIFFUSSOR: P.P.O / Aluminum / Cast Iron


#### MOTOR Single Phase Heavy Duty Continuous Work

Motor Housing: Aluminium  
Shaft: Carbon Steel / Stainless Steel  
Insulation: Class B / Class F  
Protection: IP44 / IP54  
Cooling: External ventilation

AU-JET-100L

### PERFORMANCE SPECIFICATIONS

Model	Power		Q.max. L/min	H.max. m	Suct.max. m	Speed r.p.m	Inlet/Outlet mm	PACKAGE DIMENSIONS & G.W.				
	HP	kW						A	B	H	kg	1x20"FCL
AU-JET-60L	0.60	0.46	42	38			25x25	480	210	220	15.2	1320PCS
AU-JET-80L	0.80	0.60	48	46	9	2850	25x25	480	210	220	16.2	1320PCS
AU-JET-100L	1.0	0.75	52	51			25x25	480	210	220	17.2	1320PCS



\* 110V, 110V/220V, 60Hz etc. models are available on request.