

AU-JET-S Series SELF-PRIMING PUMP

AU-JET-S series self-priming pumps are high efficient jetting pump with excellent suction even when there are air bubbles. The pump consists a single impeller, centrifugal pump and a nozzle with a jet pipe. The series pumps are particularly suitable for water supplying in domestic installations, small-scale agriculture watering and where self-priming operation is demanded.



AU-JET-100S

CONSTRUCTION:

PUMP Peripheral

Pump Body: Cast Iron

Impeller: Brass / P.P.O. Plastics

Mechanical Seal: Carbon / Ceramic / Stainless steel

MOTOR Single Phase Heavy Duty Continuous Work

Motor Housing: Aluminum

Shaft: Carbon Steel / Stainless Steel


Insulation: Class B / Class F

Protection: IP44 / IP54

Cooling: External ventilation

PERFORMANCE SPECIFICATIONS

Model	Power		Q.max. L/min	H.max. m	Suct.max. m	Speed r.p.m	Inlet/Outlet mm	PACKAGE DIMENSIONS & G.W.				
	HP	kW						A	B	H	kg	1x20"FCL
AU-JET-60S	0.6	0.46	40	38			25x25	420	210	220	13.6	1420PCS
AU-JET-80S	0.8	0.60	46	45	9	2850	25x25	420	210	220	14.6	1420PCS
AU-JET-100S	1	0.75	52	50			25x25	420	210	220	15.6	1420PCS



* 110V, 110V/220V, 60Hz etc. models are available on request.